



**IN STOCK AT  
JOHNSON VALVES**


**TEL 023 80 669666**

**262/106  
GENERAL PURPOSE  
NORMALLY CLOSED**



**ASCO JOUCOMATIC  
SERIES 262 - DIRECT OPERATED  
SERIES 106 - DIRECT OPERATED**


FOR USE ON AIR INERT GAS  
WATER & LIGHT OIL



### Series 262

Minimum pressure 0 bar

Fig No	BSP	A	B	Orifice Size	MAX PRESSURE BAR						SPARES KIT NO		COIL SIZE	
					AIR		WATER		LT OIL		AC	DC	AC	DC
					AC	DC	AC	DC	AC	DC				
SCE262C001	1/8	30	65	1.2	50	45	50	45	35	35	K182-026	K089-854	M6-FT	M6-FT
SCE262C002	1/8	30	65	3.2	11	5	12	5	9	5	K89-211	K89-854	M6-FT	M6-FT
SCE262C019	1/4	40	75	1.2	50	35	50	35	35	35	K92-648	K93-070	M6-FT	M6-FT
SCE262C020	1/4	40	75	2.4	25	10	25	8	11	8	K92-648	K93-070	M6-FT	M6-FT
SCE262C022	1/4	40	75	3.2	9	4	11	4	6	4	K92-648	K93-070	M6-FT	M6-FT
SCE262C090	1/4	40	75	7.1	1.8	1	2.5	1	1.9	1	K97-845	K93-070	M6-FT	M6-FT



### Series 106

Minimum Pressure 0 bar

Fig No	BSP	A	B	Orifice Size	MAX PRESSURE BAR						SPARES KIT NO		COIL SIZE	
					AIR		WATER		LT OIL		AC	DC	AC	DC
					AC	DC	AC	DC	AC	DC				
106-00-001	1/8	33	52	1	20	20	20	20	20	20	—	—	M22-4W	M22-4W
106-00-003	1/8	33	52	2.5	10	4	10	4	10	4	—	—	M22-4W	M22-4W
106-00-058	1/8	33	52	1.5	20	12	20	12	20	12	—	—	M22-4W	M22-4W
106-00-187	1/4	40	60	1.5	20	12	20	12	20	12	—	—	M22-4W	M22-4W
106-00-189	1/4	40	60	2.5	10	4	10	4	10	4	—	—	M22-4W	M22-4W
106-00-258	1/4	40	60	2.5	14	7	14	7	14	7	—	—	M25-5W	M25-5W

Here we show a selection of Asco Joucomatic brass general purpose valves for the automatic control of air, inert gas, water, light oil and other gases and liquids compatible with the materials used.

The 262 series valves are robustly manufactured and are more suited to industrial applications and do not need a minimum operating pressure.

The 106 series offers a cost effective compact alternative. Which has a integral manual operator fitted as standard.

These brass solenoid valves are normally closed: (open when energised and closed when de-energised).

#### Features and Benefits.

- No minimum operating pressure required.
- Coil easily removed with valve in position.
- Optional diaphragm materials can be supplied to suit other fluids.
- Spares kits and coils available from stock.
- Can be mounted in any position
- Manual operator supplied as standard on 106 series valves.

#### Technical Data.

Temperature range:-

-20°C to +90°C

Epoxy moulded coils IP65 rated

Standard voltages

AC 24v/110v/115v/230v

DC 12v/24v

Body material brass

NBR (nitrile/buna-n) seals

**For normally open versions  
please contact sales.**

**ASCO JOUCOMATIC AUTHORISED DISTRIBUTOR**